

CRYSTAL PLUS OIL 200T

Crystal Plus Oil is an odorless, tasteless, crystal clear, technical grade white mineral oil. It meets or exceeds requirements of US FDA regulation 21 CFR 178.3620 (b). This oil also meets USDA requirements for H-1 lubricants for incidental food contact.

Features

- Excellent lubricity
- Economical for users who require white oils,
- Variable viscosities available upon request

Applications

- Lubricant for drawing, stamping, forming and rolling of aluminum foil
- Fiber lubricant for textile fibers/fabric
- Plasticizer for rubber used on conveyor belts; also used in hoses, rollers, etc.
- De-foamer in manufacturing of paper and adhesives
- Lubricant cleaner and rust preventative
- Component of animal feed to reduce dusting and enhance appearance in dry feeds and mineral supplements. Up to 3.0 percent in mineral supplements and to 0.06 percent maximum in finish feed

Typical Properties	ASTM Test Methods	200FG
Gravity, °API	D287	32.0
Specific Gravity @ 25°C	D1298	.856
Viscosity, SUS @ 100°F	D2161	205
Viscosity, cST.@ 40°C	D445	39.9
Pour Point, °F	D97	+15
Color, Saybolt	D156	+30
Flash Point, COC°F	D92	410

Note: The oil above is colorless, odorless, and tasteless and surpasses requirements of FDA and US Pharmacopeia standards for Neutrality, Sulfur Compounds Solid Parafins and Carbonizable Substances.

Consult the Material Safety Data Sheet (MSDS) for safety and handling information. To obtain and MSDS, call (512) 396-3399 ext 24.